

Product Specifications **DT4xW Desktop Printer**

Model		DT4xW
Print Method		Direct Thermal
Resolution		203 dpi (8 dot/mm)
Print Speed		7 IPS (177 mm/s)
Print Width		4.25" (108 mm)
Print Length		Min. 0.16" (4 mm)**; Max. 68" (1727 mm)
Memory	Flash	128 MB Flash (60 MB for user storage)
	SDRAM	32 MB
Sensor Type		Fixed transmissive sensor, central aligned Adjustable reflective sensor
Media	Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
	Width	1" (25.4 mm) Min. - 4.64" (118 mm) Max.
	Thickness	0.003 " (0.076 mm) Min. -0.008 " (0.203 mm) Max.
	Label Roll Diameter	Max. 5" (127 mm)
	Core Diameter	1", 1.5" (25.4 mm, 38.1 mm)
Printer Language		EZPL, GEPL, GZPL, GDPL auto switch
Software	Label Design Software	GoLabel (for EZPL only)
	Driver	Windows 2000, XP, Vista, Windows 7, 8 & 8.1, 10, 11, Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019, 22, MAC, Linux
	SDK	Win CE,.NET, Windows Vista, Windows 7, Windows 8 & 8.1, Windows 10, Android, Mac. iOS
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions
		TTF Fonts
	Download Fonts	Bitmap Fonts
Asian Fonts		90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions
TTF Fonts		TTF Fonts (Bold / Italic / Underline). 90°, 180°, 270° rotatable
Barcodes	1-D Bar Codes	China Postal Code, Codabar, code 11, code 32, code 39, Code 93, Code 128 (subset A,B,C), EAN-8/EAN-13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, Industrial 2 of 5, Interleaved 2-of-5 with Shipping Bearer Bars, ISBT-128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Plante 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-W (with 2 or 5 digit extension), UCC/EAN-128-K-Mart and Random Weight
	2-D Bar Codes	Aztec code, Code 49, Codablock G, Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417, QR code, TLC 39, GS1 Composite
Code Pages		Codepage 437, 737, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869 Windows 1250, 1251, 1252, 1253, 1254, 1255, 125 Unicode UTF8, UTF16BE, UTF16LE
Graphics		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software
Interfaces		Serial port: RS-232 (DB-9)
		USB Device port (B-Type)
		IEEE 802.3 10/100 Base-Tx Ethernet port (RJ-45)
		USB Host (A-Type)
Control Panel		1 Control key: FEED/PAUSE/CANCEL with dual color LED backlight: Ready(Green); Error (Red)
Power		Auto Switching 100-240VAC, 50-60Hz
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)
	Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Humidity	Operation	25-85%, non-condensing
	Storage	10-90%, non-condensing
Agency Approvals		CE (EMC), FCC Class A, CB
Dimension	Length	8.58" (218 mm)
	Height	6.53" (166 mm)
	Width	6.61" (168 mm)
Weight		3.17 lbs(1.44 Kg), excluding consumables
Options & Accessories		Cutter Module
		Label Dispenser
		Wireless LAN (IEEE 802.11 b/g/n)
		Bluetooth
		Real Time Clock
		External label roll holder for 10" (254 mm) O.D. label rolls External label rewriter

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.
 ** Minimum print height specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc.
 Godex is pleased to test non-standard materials for minimum height printing capability.



www.godexintl.com

Godex Europe GmbH, Industriestrasse 19, D-42477 Radevormwald, Geschäftsführer: Roy Theisen, Alberta Tai,
 Handelsregister-Nr. HRB 50788, Amtsgericht Köln, Ust.-IdNr. DE813195023, Steuer-Nr. 221/5743/2628, WEEE Reg.-Nr. DE45355452.